

**Amendments to the Claims:**

This listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A thermoelectric effect device, comprising:

two thermoelectric converter elements ~~including~~ comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member, and

connecting one [[of the]] electric conduction ~~materials~~ material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has an endothermic section and an exothermic section,

~~characterized in that~~ wherein:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_{\alpha}$  at the endothermic section and a temperature  $T_{\beta}$  at the exothermic section as to keep a relation  $T_{\alpha} < T_{\beta}$ .

2. (Currently Amended) A thermoelectric effect device, comprising:

2n pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the 2n pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the 2n pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming an endothermic section and an exothermic section, and

connecting at least a part of the electric conduction material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has n piece of the endothermic section and n piece of the exothermic section,

~~characterized in that~~ wherein:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_\alpha$  at the endothermic section and a temperature  $T_\beta$  at the exothermic section as to keep a relation  $T_\alpha > T_\beta$ .

3. (Currently Amended) An energy direct conversion system, comprising:

two thermoelectric converter elements ~~including~~ comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member,

the first thermoelectric converter element and the second thermoelectric converter element being disposed in ambient temperatures different from each other, and

a distance being secured for so keeping an ambient temperature  $T_1$  of the thermoelectric converter element on a high temperature side and an ambient temperature  $T_2$  of the thermoelectric converter element on a low temperature side as to keep a relation  $T_1 > T_2$ ,

~~characterized in that~~ wherein:

taking out an electric potential energy from a certain section of the electric conduction material constitutes a direct energy conversion electric circuit system converting from a heat energy into the electric potential energy.

4. (Currently Amended) An energy direct conversion system, comprising:

2n pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the 2n pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the 2n pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming ambient temperatures different from each other, and

a distance being secured for so keeping an ambient temperature  $T_1$  of the thermoelectric converter element on a high temperature side and an ambient temperature  $T_2$  of the thermoelectric converter element on a low temperature side as to keep a relation  $T_1 > T_2$ ,

~~characterized in that~~ wherein:

taking out an electric potential energy from a certain section of the electric conduction material constitutes a direct energy conversion electric circuit system converting from a heat energy into the electric potential energy.

5. (Currently Amended) The energy direct conversion system, as claimed in claim 3, wherein,

the energy direct conversion system further comprises:

at least a pair of the direct energy conversion electric circuit systems, and

a plurality of starting sections using a temperature difference attributable to one of an initial external heating and an initial external cooling,

~~characterized in that~~ wherein:

the energy direct conversion system converts a heat energy source directly into the electric potential energy, wherein the heat energy source is in different ambient temperatures in different places independent of each other.

6. (Currently Amended) An energy conversion system ~~characterized in that~~ wherein the energy conversion system converts the electric potential energy into a chemical potential energy through an electrolyzation, the electric potential energy being obtained from the heat

energy direct conversion system as claimed in claim 3.

7. (Currently Amended)      An energy conversion system ~~characterized in that:~~ wherein the energy conversion system converts the electric potential energy into a chemical potential energy through an electrolyzation, the electric potential energy being obtained from the heat energy direct conversion system as claimed in claim 4.

8. (Currently Amended)      An energy conversion system, comprising:

    a thermoelectric effect device comprising: ~~including~~;

        two thermoelectric converter elements ~~including~~ comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

        by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member, and

        connecting one [[of the]] electric conduction ~~materials~~ material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has an endothermic section and an exothermic section,

~~the thermoelectric effect device characterized in that:~~ wherein

        between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_{\alpha}$  at the endothermic section and a temperature  $T_{\beta}$  at the exothermic section as to keep a relation  $T_{\alpha} < T_{\beta}$ ,

~~the energy conversion system characterized in that:~~ wherein

        the energy conversion system obtains the electric potential energy by supplying to the energy direct conversion system as claimed in claim 3 the heat energy obtained from the thermoelectric effect device, and that

the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

9. (Currently Amended) An energy conversion system, comprising:

a thermoelectric effect device ~~including~~ comprising:

two thermoelectric converter elements ~~including~~ comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member, and

connecting one [[of the]] electric conduction ~~materials~~ material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has an endothermic section and an exothermic section,

~~the thermoelectric effect device characterized in that~~ wherein:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_\alpha$  at the endothermic section and a temperature  $T_\beta$  at the exothermic section as to keep a relation  $T_\alpha < T_\beta$ ,

~~the energy conversion system characterized in that~~ wherein:

the energy conversion system obtains the electric potential energy by supplying to the energy direct conversion system as claimed in claim 4 the heat energy obtained from the thermoelectric effect device, and that

the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

10. (Currently Amended) An energy conversion system, comprising:

a thermoelectric effect device ~~including~~; comprising:

two thermoelectric converter elements ~~including~~ comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member, and

connecting one [[of the]] electric conduction ~~materials~~ material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has an endothermic section and an exothermic section,

the thermoelectric effect device characterized in that:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_\alpha$  at the endothermic section and a temperature  $T_\beta$  at the exothermic section as to keep a relation  $T_\alpha > T_\beta$ ,

the energy conversion system characterized in that:

the energy conversion system obtains [[the]] electric potential energy by supplying to the energy direct conversion system as claimed in claim 5 the heat energy obtained from the thermoelectric effect device, and that

the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

11. (Currently Amended) An energy conversion system, comprising:

a thermoelectric effect device ~~including~~; comprising:

2n pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the 2n pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the 2n pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming an endothermic section and an exothermic section, and

connecting at least a part of the electric conduction material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has n piece of the endothermic section and n piece of the exothermic section,

the thermoelectric effect device characterized in that:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_{\alpha}$  at the endothermic section and a temperature  $T_{\beta}$  at the exothermic section as to keep a relation  $T_{\alpha} < T_{\beta}$ ,

the energy conversion system characterized in that: the energy conversion system obtains [[the]] electric potential energy by supplying to the energy direct conversion system as claimed in claim 3 the heat energy obtained from the thermoelectric effect device, and that

the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

12. (Currently Amended) An energy conversion system, comprising:

a thermoelectric effect device ~~including~~; comprising:

2n pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the  $2n$  pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the  $2n$  pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming an endothermic section and an exothermic section, and

connecting at least a part of the electric conduction material to a direct current source in-line constituting a Peltier effect heat transfer circuit system which has  $n$  piece of the endothermic section and  $n$  piece of the exothermic section,

the thermoelectric effect device characterized in that:

between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_\alpha$  at the endothermic section and a temperature  $T_\beta$  at the exothermic section as to keep a relation  $T_\alpha > T_\beta$ ,

the energy conversion system characterized in that:

the energy conversion system obtains [[the]] electric potential energy by supplying to the energy direct conversion system as claimed in claim 4 the heat energy obtained from the thermoelectric effect device, and that the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

13. (Currently Amended) An energy conversion system, comprising:

a thermoelectric effect device ~~including;~~ comprising;

$2n$  pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the  $2n$  pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the  $2n$  pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming an endothermic section and an exothermic section, and connecting at least a part of the electric conduction material to a direct current source in-



line constituting a Peltier effect heat transfer circuit system which has n piece of the endothermic section and n piece of the exothermic section,

the thermoelectric effect device characterized in that: between the endothermic section and the exothermic section, a distance is secured for so keeping a temperature  $T_{\alpha}$  at the endothermic section and a temperature  $T_{\beta}$  at the exothermic section as to keep a relation  $T_{\alpha} < T_{\beta}$ ,

the energy conversion system characterized in that:

the energy conversion system obtains [[the]] electric potential energy by supplying to the energy direct conversion system as claimed in claim 5 the heat energy obtained from the thermoelectric effect device, and that

the energy conversion system uses a part of the electric potential energy as a direct current source by feedbacking the part of the electric potential energy to the thermoelectric effect device.

14. (Original) The energy conversion system as claimed in claim 8, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

15. (Original) The energy conversion system as claimed in claim 9, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

16. (Original) The energy conversion system as claimed in claim 10, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

17. (Original) The energy conversion system as claimed in claim 11, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

18. (Original) The energy conversion system as claimed in claim 12, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

19. (Original) The energy conversion system as claimed in claim 13, wherein the feedback of the electric potential energy is controlled by turning on and off a switch.

20. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 8, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

21. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 9, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

22. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 10, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

23. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 11, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

24. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 12, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

25. (Currently Amended) The ~~heat~~ energy conversion system as claimed in claim 13, wherein the feedback of the electric potential energy is controlled by turning on and off a switch, so that the electric potential energy is supplied to the thermoelectric effect device and that an electric power from the direct current source of the thermoelectric effect device is cut.

26. (Currently Amended) An energy direct conversion system ~~characterized in that~~ comprising:

two thermoelectric converter elements comprising a first thermoelectric converter element and a second thermoelectric converter element each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the first electric conductor member's side opposite to the joint member and the second electric conductor member's side opposite to the joint member being electrically connected, respectively, to a facing first electric conductor member's side opposite to a facing joint member and a facing second electric conductor member's side opposite to the facing joint member,

the first thermoelectric converter element and the second thermoelectric converter element being disposed in ambient temperatures different from each other, and

a distance being secured for so keeping an ambient temperature T1 of the thermoelectric converter element on a high temperature side and an ambient temperature T2 of the thermoelectric converter element on a low temperature side as to keep a relation  $T1 > T2$ ,

wherein:

taking out an electric potential energy from a certain section of the electric conduction material constitutes a direct energy conversion electric circuit system converting from a heat energy into the electric potential energy;

the energy conversion system converts the electric potential energy into a chemical potential energy through an electrolization, the electric potential energy being obtained from the ~~energy conversion system as claimed in claim 6~~ heat energy direct conversion system.

27. (Currently Amended) An energy direct conversion system ~~characterized in that:~~ comprising:

2n pieces of thermoelectric converter elements each of which is formed in such a manner as to join, by using a joint member, a first electric conductor member and a second electric conductor member which have different Seebeck coefficients from each other,

by way of an electric conduction material, the 2n pieces of the thermoelectric converter elements being electrically connected to each other in such a manner as to form an in-line,

the 2n pieces of the thermoelectric converter elements adjacent to each other being disposed alternately, thus forming ambient temperatures different from each other, and a distance being secured for so keeping an ambient temperature T1 of the thermoelectric converter element on a high temperature side and an ambient temperature T2 of the thermoelectric converter element on a low temperature side as to keep a relation  $T1 > T2$ ,

wherein:

taking out an electric potential energy from a certain section of the electric conduction material constitutes a direct energy conversion electric circuit system converting from a heat energy into the electric potential energy; and

the energy direct conversion system converts the electric potential energy into a chemical potential energy through an electrolyzation, the electric potential energy being obtained from the heat energy direct conversion system ~~energy conversion system as claimed in claim 7.~~

28. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the energy conversion system as claimed in claim 8.

29. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the energy conversion system as claimed in claim 9.

30. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the

energy conversion system as claimed in claim 10.

31. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the energy conversion system as claimed in claim 11.

32. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the energy conversion system as claimed in claim 12.

33. (Currently Amended) An energy conversion system wherein ~~characterized in that:~~ the energy conversion system converts the electric potential energy into a chemical potential energy through the electrolyzation, the electric potential energy being obtained from the energy conversion system as claimed in claim 13.